

64333 A 40-15

Halogen lamps with reflector, current-controlled, 30...40 W




Product family benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

Product family features

- Dimmable
- Available with connector combinations A, B, C/Z on request
- Infrared radiation output that provides light in the worst of conditions



Product datasheet

Technical data

Product information

Order reference	64333
-----------------	-------


Electrical data

Lamp current	6.6 A
Nominal wattage	40.00 W

Photometrical data

Luminous intensity	10000 cd
Axial luminous intensity	12700 cd
Color rendering index Ra	100

Dimensions & weight



Diameter	35.3 mm
Length	35.0 mm
Length with base excl. base pins/connection	37.00 mm

Lifespan

Lifespan	1500 h
----------	--------

Capabilities

Burning position	h45
Connection with cable	Yes
Mains terminals	Leads w/female flat connectors

Country specific categorizations

Order reference	64333
-----------------	-------

Product datasheet

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4008321166340 4055462135223
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321166340	OSR64333A4015	-	-	-
4008321166340	OSR64333A4015	-	-	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321166340	64333 A 40-15	Folding carton box 1	34 mm x 34 mm x 50 mm	0.06 dm ³	23.00 g
4008321166357	64333 A 40-15	Shipping carton box 20	191 mm x 81 mm x 131 mm	2.03 dm ³	450.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on airfield lamps see the brochure:

"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
