OSRAM

TRUCKSTAR PRO

Brightest OSRAM truck halogen light





Up to 2.5 times longer lifetime
Reduced downtime and fleet costs
compared to standard lamps



Up to 120% more brightness

More light allows to see farther and
therefore react sooner compared to the
minimum legal standard



Very high vibration resistanceSuitable for heavy duty applications



The most powerful halogen and signal truck lamps from OSRAM

Discover TRUCKSTAR PRO - the brightest halogen and signal truck lamps from OSRAM with excellent value for money. With extremely long life, up to 120% more light than standard lamps and very high vibration resistance these 24 volt lamps are ideal for professional drivers while reducing downtime and fleet costs. Thanks to the high vibration resistance, TRUCKSTAR PRO lamps are suitable even for heavy duty applications. Due to their impressive brightness and up to 2.5 times longer lifetime compared to standard lamps, the lamps improve your safety while driving on the road.

Product family datasheet

Technical data

| | Product information | General Product Information | Electrical Data | | |
|---------------------|---|--------------------------------|----------------------------|-----------------|--------------------|
| Product description | Application (Category and Product specific) | Global order reference | Power input | Nominal voltage | Nominal wattage |
| TRUCKSTAR PRO H1 | Halogen headlight lamp | 64155TSP | 84 W ¹⁾ | 24.0 V | 70 W |
| TRUCKSTAR PRO H3 | Halogen headlight lamp | 64156TSP | 84 W ¹⁾ | 12.0 V | 55 W |
| TRUCKSTAR PRO H4 | Halogen headlight lamp | 64196TSP | 85 / 80 W ¹⁾ | 24.0 V | 75/70 W |
| TRUCKSTAR PRO H11 | Halogen headlight lamp | 64216TSP | 80 W ¹⁾ | 24.0 V | 70 W |

| | | | | Physical Attributes & Dimensions | |
|---------------------|--------------|-----------------------|-------------------------------|----------------------------------|---------|
| Product description | Test voltage | Nominal luminous flux | Luminous flux tolerance | Lamp base | Length |
| TRUCKSTAR PRO H1 | 28.0 V | 1900 lm | ±15 % | P14.5s | 62.5 mm |
| TRUCKSTAR PRO H3 | 28.0 V | 1750 lm | ±15 % | PK22s | 42.0 mm |
| TRUCKSTAR PRO H4 | 28.0 V | 1900/1200 lm | ±15 / ±15 % | P43t | 82.0 mm |
| TRUCKSTAR PRO H11 | 28.0 V | 1600 lm | ±10 % | PGJ19-2 | 67.0 mm |

| | | Lifetime Data | Lifetime Data | | Certificates & standards | |
|---------------------|----------|----------------------------|------------------|------------|--------------------------------|--|
| Product description | Diameter | Lifespan B3 | Lifespan Tc | Technology | ECE category | |
| TRUCKSTAR PRO H1 | 9 mm | 600 hr | 1200 hr | HAL | H1 | |
| TRUCKSTAR PRO H3 | 11.0 mm | 600 hr | 1200 hr | HAL | H3 | |
| TRUCKSTAR PRO H4 | 16.5 mm | 140 / 450 hr ²⁾ | 300 / 1000 hr | HAL | H4 | |
| TRUCKSTAR PRO H11 | 12.0 mm | 500 hr | 1000 hr | HAL | H11 | |

Product family datasheet

Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

| Product description | Date of declaration | Primary article identifier | Candidate list substance 1 | Declaration no. in SCIP database | |
|---------------------|---------------------|--|----------------------------|----------------------------------|--|
| TRUCKSTAR PRO H1 | 30-08-2024 | 4062172216531 | No declarable | In work | |
| | 30 00 202 . | 4008321784209 | substances contained | work | |
| | | 4052899413832 | substances contained | | |
| | | 4052899413931 | | | |
| | | 4062172216555 | | | |
| | | 4062172159432 | | | |
| | | 4008321851765 | | | |
| | | 4062172174657 | | | |
| | | 4062172285117 | | | |
| | | 4062172233117 | | | |
| | | 4052899529229 | | | |
| | | • | | | |
| | | 4008321784179 | | | |
| | | 4052899414037 | | | |
| | | 4062172218771 | | | |
| TRUCKSTAR PRO H3 | 16-08-2024 | 4052899413856 | No declarable | In work | |
| | | 4052899413955 | substances contained | | |
| | | 4052899481893 | | | |
| | | 4058075021952 | | | |
| | | 4062172159401 | | | |
| | | 4008321784247 | | | |
| | | 4062172027410 | | | |
| | | 4008321851901 | | | |
| | | 4062172285933 | | | |
| | | 4052899481954 | | | |
| | | 4052899481916 | | | |
| | | 4052899414051 | | | |
| | | 4008321784261 | | | |
| TRUCKSTAR PRO H4 | 26-08-2024 | 4062172150439 | No declarable | In work | |
| | | 4052899476066 | substances contained | | |
| | | 4052899413979 | | | |
| | | 4062172150491 | | | |
| | | 4052899413870 | | | |
| | | 4008321785022 | | | |
| | | 4008321785077 | | | |
| TRUCKSTAR PRO H11 | 16-08-2024 | 4052899904804 | No declarable | In work | |
| | | 4052899904644 | substances contained | | |
| | | · | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | • | | | |
| | | • | | | |
| | | 4052899413993 | | | |
| | | | | | |
| TRUCKSTAR PRO H11 | 16-08-2024 | 4052899904804 4052899904644 4008321832399 4062172150552 4052899414099 4008321832368 4008321832412 4052899413894 | | In work | |

¹⁾ Maximum

²⁾ Filament 1

Product family datasheet

Download Data

| File |
|--|
| ref_pim_amsp_product360degreeimages TRUCKSTAR PRO H1 64155TSP |
| ref_pim_amsp_product360degreeimages TRUCKSTAR PRO H3 64156TSP |
| ref_pim_amsp_product360degreeimages TRUCKSTAR PRO H4 64196TSP |

Legal advice

Light output compared to the minimum ECE R112 requirements

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















