

TRUCKSTAR PRO T4W

Brightest OSRAM truck light



Excellent brightness

More light allows to see farther and therefore react sooner



More than double the service life

Reduced downtime and fleet costs compared to standard lamps



Very high vibration resistance

Suitable for heavy duty applications



The most powerful halogen truck light from OSRAM

Discover TRUCKSTAR PRO signal lamps - the brightest truck light from OSRAM with excellent value for money. With up to 100% more light than standard lamps, extremely long life and very high vibration resistance these 24 volt lamps are ideal for professional drivers while reducing downtime and fleet costs. Thanks to the high vibration resistance, TRUCKSTAR PRO lamps are suitable even for heavy duty applications. Due to their impressive brightness and more than double the service life compared to standard lamps, the lamps improve your safety while driving on the road.

Product datasheet

Technical data

Product information

| | |
|---|----------------|
| Order reference | 3930TSP |
| Application (Category and Product specific) | Auxiliary lamp |


Electrical data

| | |
|-----------------------|--------|
| Power input | 5 W |
| Nominal voltage | 24.0 V |
| Nominal wattage | 4.00 W |
| Power input tolerance | ±10 % |
| Test voltage | 28.0 V |

Photometrical data

| | |
|-------------------------|-------|
| Luminous flux | 35 lm |
| Luminous flux tolerance | ±20 % |

Dimensions & weight



| | |
|----------------|---------|
| Length | 27.4 mm |
| Diameter | 9 mm |
| Product weight | 2.03 g |

Lifespan

| | |
|-------------|--------|
| Lifespan B3 | 550 h |
| Lifespan Tc | 1000 h |

Additional product data

| | |
|-----------------------------|------|
| Base (standard designation) | BA9s |
|-----------------------------|------|

Product datasheet

Capabilities

| | |
|------------|-----|
| Technology | AUX |
|------------|-----|

Certificates & standards

| | |
|--------------|-----|
| ECE category | T4W |
|--------------|-----|

Country specific categorizations

| | |
|-----------------|---------|
| Order reference | 3930TSP |
|-----------------|---------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---|--|
| Date of Declaration | 05-03-2024 |
| Primary Article Identifier | 4008321174055 4008321130846 4008321795106 4008321842589 4062172158336 |
| Candidate List Substance 1 | No declarable substances contained |
| Declaration No. in SCIP database | In work |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4008321174055 | TRUCKSTAR PRO T4W | Blister 2 | 135 mm x 95 mm x 13 mm | 0.17 dm ³ | 15.00 g |
| 4008321174062 | TRUCKSTAR PRO T4W | Shipping carton box 20 | 146 mm x 145 mm x 106 mm | 2.24 dm ³ | 197.67 g |
| 4008321795106 | TRUCKSTAR PRO T4W | Unpacked 1 | 9 mm x 9 mm x 27 mm | 0.00 dm ³ | 2.00 g |
| 4008321795113 | TRUCKSTAR PRO T4W | Folding carton box 10 | 46 mm x 29 mm x 112 mm | 0.15 dm ³ | 31.00 g |
| 4008321795120 | TRUCKSTAR PRO T4W | Shipping carton box 50 | 148 mm x 115 mm x 55 mm | 0.94 dm ³ | 187.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet



OSRAM