

# ORIGINAL - METAL BASE P21/5W

Original spare part



## The cost-effective original spare parts for trucks

Discover OSRAM's ORIGINAL signal lamps with metal bases - high-quality original spare parts for 24 volt lamps. Due to the wide product range, the lamps can be used for different applications: as position and parking lights, indicator, brake, fog and reversing lights as well as number plate and side position lights.

# Product datasheet

## Technical data

### Product information

|   |                |
|---|----------------|
| Order reference                             | 7537           |
| Application (Category and Product specific) | Auxiliary lamp |


### Electrical data

|                       |                     |
|-----------------------|---------------------|
| Power input           | 28 / 10 W           |
| Nominal voltage       | 24.0 V              |
| Nominal wattage       | 21/5 W              |
| Power input tolerance | $\pm 6 / \pm 10 \%$ |
| Test voltage          | 28.0 V              |

### Photometrical data

|                         |                      |
|-------------------------|----------------------|
| Luminous flux           | 440/40 lm            |
| Luminous flux tolerance | $\pm 15 / \pm 20 \%$ |

### Dimensions & weight



|                |         |
|----------------|---------|
| Length         | 52.5 mm |
| Diameter       | 27.0 mm |
| Product weight | 8.10 g  |

### Lifespan

|             |              |
|-------------|--------------|
| Lifespan B3 | 65 / 600 h   |
| Lifespan Tc | 600 / 1600 h |

### Additional product data

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | BAY15d |
|-----------------------------|--------|

## Product datasheet

### Capabilities

|            |     |
|------------|-----|
| Technology | AUX |
|------------|-----|

### Certificates & standards

|              |        |
|--------------|--------|
| ECE category | P21/5W |
|--------------|--------|

### Country specific categorizations

|                 |      |
|-----------------|------|
| Order reference | 7537 |
|-----------------|------|

### Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |   |
|---|---|
| Date of Declaration   | 06-03-2024  |
| Primary Article Identifier  | 4050300838038   4050300925943   4008321630124   4008321773449   4008321857071   4052899402232   4052899423671   4062172121354   4062172375078   4062172375047 |
| Candidate List Substance 1  | No declarable substances contained  |
| Declaration No. in SCIP database                                      | In work   |

### Country specific information

| Product code  | METEL code | SEG-No. | STK number | UK Org |
|---------------|------------|---------|------------|--------|
| 4050300838038 | OSRA7537   | -       | 4739970    | -      |
| 4050300524863 | OSRA7537   | -       | 4739970    | -      |
| 4050300838038 | OSRA7537   | -       | 4739970    | -      |

### Logistical Data

| Product code  | Product description          | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume               | Gross weight |
|---------------|------------------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4050300838038 | ORIGINAL - METAL BASE P21/5W | Unpacked<br>1                | 27 mm x 27 mm x 53 mm                | 0.04 dm <sup>3</sup> | 8.00 g       |
| 4050300524863 | ORIGINAL - METAL BASE P21/5W | Folding carton box<br>10     | 58 mm x 54 mm x 139 mm               | 0.44 dm <sup>3</sup> | 103.00 g     |
| 4008321091109 | ORIGINAL - METAL BASE P21/5W | Shipping carton box<br>50    | 273 mm x 145 mm x 65 mm              | 2.57 dm <sup>3</sup> | 565.00 g     |
| 4050300925943 | ORIGINAL - METAL BASE P21/5W | Blister<br>2                 | - x - x -                            |                      |              |
| 4008321141545 | ORIGINAL - METAL BASE P21/5W | Shipping carton box<br>20    | 280 mm x 80 mm x 103 mm              | 2.31 dm <sup>3</sup> | 307.00 g     |

## Product datasheet

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM