

## HMI DIGITAL 6000 W

HMI DIGITAL | Metal halide lamps, single-ended



### Areas of application

- Studio
- Stage
- TV

### Product family benefits

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

### Product family features

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Hot restart capability



# Product datasheet

## Technical data

### Electrical data

|                 |           |
|-----------------|-----------|
| Nominal wattage | 6000.00 W |
| Nominal voltage | 123 V     |
| Nominal current | 55 A      |

### Photometrical data

|                          |           |
|--------------------------|-----------|
| Nominal luminous flux    | 600000 lm |
| Color temperature        | 6000 K    |
| Color rendering index Ra | 90        |

### Dimensions & weight

|          |          |
|----------|----------|
| Diameter | 75.0 mm  |
| Length   | 360.0 mm |

### Lifespan

|          |       |
|----------|-------|
| Lifespan | 500 h |
|----------|-------|

### Additional product data

|                             |      |
|-----------------------------|------|
| Base (standard designation) | GX38 |
|-----------------------------|------|

### Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |  |
|---|--|
| Date of Declaration   | 06-03-2024   |
| Primary Article Identifier  | 4062172005890  |
| Candidate List Substance 1  | Lead   |
| CAS No. of substance 1  | 7439-92-1  |
| Safe Use Instruction  | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database                                      | 7c5a8266-8f2a-43a1-95b8-5931d68b0df1   |

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Logistical Data

| Product code  | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume                | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4062172005890 | HMI DIGITAL 6000 W  | Shipping carton box<br>1     | 715 mm x 240 mm x<br>240 mm          | 41.18 dm <sup>3</sup> | 2211.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.