OSRAM

LEDriving FL PSX24W





Cool White color temperature of 6,000 K

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



Superior brightness

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



Ultra compact LED replacement for conventional PSX24W fog lamps as socket solution

Easy installation with optimized compatibility



New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps with state-of-the-art LED technology. The color temperature of 6,000K provides for a stylish cool white look and improved visibility.

Product family datasheet

Technical data

	Product in	nformation		General Product Information		Electrical Data	
Product description		Application (Category and Product specific)		Global order reference		Nominal voltage	Nominal wattage
LEDriving FL ≙ PSX24W	Mainly used for headlight/ fog light applications		Off-road ≙ PSX24W	2604CW		12.0 V	6 W
			Photometric Data			Physical Attributes & Dimensions	Lifetime Data
Product description	Test voltage		Luminous flux tolerance	Nominal luminous flux		Diameter	Lifespan Tc
			toterance				
LEDriving FL ≙ PSX24W	13.2 V		±20 %	730 lm		18.0 mm	5000 hr
LEDriving FL ≙ PSX24W	13.2 V	Capabilities	±20 %	730 lm ental & Regula on according Ar on (EC) 1907/20	t. 33 of EU	ation	5000 hr
LEDriving FL ≜ PSX24W Product description	13.2 V Lifespan B3	Capabilities Technology	±20 % Environme Informatic Regulation	ental & Regula on according Ar on (EC) 1907/20 ticle	t. 33 of EU	ation) n no. in	5000 hr

Product family datasheet

Download Data

File



Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.LEDriving CANBUS CONTROL UNIT (LEDCBCTRL102) avoids error messages on the board computer when using LED fog lights within 21 W applicationsRefer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















