Product family datasheet



# Lightbar SX180-SP

Improved safety on-road and off-road with the full force of LEDs





Compact housing design Compact mounting dimensions enables a wide range of possible applications



Lighting distance up to 190 meters Increased far field illumination



Spot Beam Highly concentrated light beam



# Durable and robust LED auxiliary light with certified approval for use on roads

Bright light is particularly critical on unlit streets and dirt roads. It lets drivers identify obstacles on the road far in advance. With its six high-performance LEDs, the LEDriving Lightbar SX180-SP automotive auxiliary light gives drivers better visibility and improved safety on the road. And the LED auxiliary light also impresses at shorter distances. With an illuminance of one lux and a beam angle of eight degrees, the beam of light can reach up to 190 meters. That's sufficient enough to identify obstacles on the road far in advance. The sophisticated reflector design of the LED search light provides very high optical efficiency with uniform light distribution and reduced glare. Reduced glare is especially relevant for oncoming traffic and counts as another important aspect of road safety.Beyond its light output, the LED high beam enhances the off-road style of the vehicle. Because the LED auxiliary light with certified approval is intended for roads, its use is not limited to off-road terrain. Various mounting options & durabilityIt goes without saying that the LED auxiliary light has to withstand quite a bit when used almost daily. Its hardwearing polycarbonate lens allows it to meet even the toughest demands while extending the lifespan of the auxiliary light for automobiles. An integrated driver and thermal management system prevents possible damage from overheating. Over and under voltage protection automatically breaks the circuit when power exceeds the predetermined current for a specified amount of time. Even major temperature fluctuations aren't a problem for the LEDriving Lightbar SX180-SP LED auxiliary lights. They work whether the air temperature is a very cold -30 or a hot 60 degrees Celsius. This is a very helpful feature, particularly during off-road tours.Its compact mounting dimensions allow the LED working light to be mounted in a variety of ways. The LED auxiliary light can be easily installed even on the front end of 4x4 and off-road vehicles as well as utility and industrial vehicles.

# Product family datasheet

# Technical data

|                     | Product information                            | General Product<br>Information                                                                                  |                         | Electrical Data               | Photom<br>etric<br>Data |                 |                              |  |
|---------------------|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|-------------------------|-------------------------------|-------------------------|-----------------|------------------------------|--|
| Product description | Application (Category<br>and Product specific) | Global order<br>reference                                                                                       |                         | Nominal wattage               |                         | Test<br>voltage | Nominal<br>luminou<br>s flux |  |
| Lightbar SX180-SP   | Additional high beam application               | LEDDL105-SP 14 W                                                                                                |                         |                               | 13.5 V                  | 1300 lm         |                              |  |
|                     | Lifetime Data                                  | Capabilities                                                                                                    | Certific<br>standar     |                               | Logistical data         |                 |                              |  |
| Product description | Lifespan Tc                                    | Technology                                                                                                      | ECE reference<br>number |                               | Commodity code          |                 |                              |  |
| Lightbar SX180-SP   | 5000 hr                                        | LED                                                                                                             | 10                      | 851220009000                  |                         |                 |                              |  |
|                     | -                                              | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |                         |                               |                         |                 |                              |  |
| Product description | Date of declaration                            | Primary article<br>identifier                                                                                   | 2                       | Candidate list<br>substance 1 |                         | CAS No. of<br>1 | substance                    |  |
| Lightbar SX180-SP   | 19-08-2024                                     | 4052899595415                                                                                                   |                         | Lead                          |                         | 7439-92-1       |                              |  |

| Product description | Safe use instruction                                                                                              | Declaration no. in<br>SCIP database          |
|---------------------|-------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| Lightbar SX180-SP   | The identification of<br>the Candidate List<br>substance is<br>sufficient to allow<br>safe use of the<br>article. | a1bdcbc4-aa38-<br>44ed-b994-<br>4a48e9654415 |

# Product family datasheet

## Download Data

|   | File                                                                                                       |
|---|------------------------------------------------------------------------------------------------------------|
| ▶ | User instruction<br>LEDriving                                                                              |
| D | Movie application<br>LEDriving D and W Image Video Bringing light to life (EN)                             |
| D | Movie application<br>Working and Driving Lights Amarok Winter                                              |
| D | Movie application<br>LEDriving Driving and Working Lights Reference Video (EN)                             |
| D | Movie application<br>OSRAM LEDdriving and working lights Imagefilm (EN)                                    |
| D | Movie application<br>LEDriving driving & working lights in application (EN)                                |
| D | Movie application<br>OSRAM Quality Testing LEDriving working and driving lights (EN)                       |
| D | Video<br>Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)                   |
| D | Video<br>OSRAM LEDriving driving and working lights: The night doesn't stand a chance                      |
| D | Video<br>OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN) |
| D | Video<br>Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads  |
|   | ref_pim_amsp_product360degreeimages<br>LEDriving Lightbar LEDDL105-SP                                      |

### Legal advice

In vehicles with 12/24 volts, auxiliary lights must be installed in pairsPrecise terms and conditions at: www.osram.com/guarantee

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











