# **OSRAM**

# NIGHT BREAKER LED START H7



The NIGHT BREAKER LED family - OSRAMs first street-legal<sup>1)</sup> LED retrofit lamps.



Up to 230% more brightness<sup>2)</sup> & 6000K

See and be seen with OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night and in adverse weather conditions.



Up to 5 times longer lifetime 3)

Vibration resistant, environmentally friendly, and cost-efficient



3 Year OSRAM Guarantee<sup>4)</sup>

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers



Start into the world of street-legal 1) LED replacement lamps with OSRAMs NIGHT BREAKER LED START.

With a revised basic design, basic features and basic benefits, the NIGHT BREAKER LED START focuses on the fundamental factors of street-legal LED replacement lamps. More and better vision and visibility and therefore more driving comfort, environmental friendliness and cost efficiency thanks to less replacement cycles and a more modern look.

Affordable products for entry into the street-legal LEDr world without having to compromise on the key advantages. With OSRAMs street-legal 1) retrofit lamps, you can benefit from highly energy-efficient, bright and modern LED light. You can now upgrade the function of your high- and low beam lights of the vehicle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with up to 230% more brightness<sup>2)</sup>, while the glare of other road users falls below the permissible maximum values by up to 50%<sup>2)</sup> In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 60% less energy and convince thanks to the LED technology and the specially developed vibration-resistant design, with up to 5 times longer life time<sup>3)</sup>. You can now replace your vehicle

## Product family datasheet

lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps 4)

Product family datasheet | NIGHT BREAKER LED START H7 © 2025, OSRAM GmbH. All rights reserved.

## Product family datasheet

### Technical data

|                            | Product in  | formation                                   |   |  |  |                         |  |                  |  |
|----------------------------|---|---|---|--|--|-------------------------|--|------------------|--|
| Product description        | Product legal advice                              |   | Product legal advice<br>3                           |  | Product legal advice<br>2  |                         | Product legal advice<br>1  |                  |  |
| NIGHT BREAKER START H7 LED | 4) For preconditions refer to: www.osra guarantee | s please<br>m.com/am-                       | 3) In comparison to<br>traditional Halogen<br>lamps |  | 2)Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 60% |                         | 1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led |                  |  |
|                            |   |   |   | General Product<br>Information   |  | ta                      |  |                  |  |
| Product description        |   | Application (Category and Product specific) |   | Global order reference   |  | Nominal voltage N       |  | Nominal wattage  |  |
| NIGHT BREAKER START H7 LED | High and  | High and low beam                           |   | 64210DWNBST-2HB  |  |                         | 16 W   |                  |  |
|                            | Photomet  | Photometric Data                            |   | Physical Attrib  |  | Attributes & Dimensions |  | Lifetime<br>Data |  |
| Product description        | Color tem   | Color temperature                           |   | Produc   | t weight   | Length                  | l  | Lifespan<br>Tc   |  |
| NIGHT BREAKER START H7 LED | 6000 K  |   | Cool white  | 58.00 g  | 9  | 77.9 m                  | m  | 2500 hr          |  |
|                            |   | Capabilities                                | Certificates<br>&<br>standards                      | Environmental & Regulatory Information<br>Information according Art. 33 of EU<br>Regulation (EC) 1907/2006 (REACh) |  |                         |  |                  |  |
| Product description        | Lifespan<br>B3                                    | Technology                                  | ECE category  | Prima<br>ident   | ary article<br>ifier   |                         | date list<br>ance 1  |                  |  |
| NIGHT BREAKER START H7 LED | 1500 hr   | LED   |   | 4062   | 172410984  | Lead                    |  |                  |  |

| Product description        | CAS No. of substance | Safe use instruction  | Declaration no. in<br>SCIP database          |
|----------------------------|----------------------|---|--|
| NIGHT BREAKER START H7 LED | 7439-92-1            | The identification of<br>the Candidate List<br>substance is<br>sufficient to allow<br>safe use of the<br>article. | caa35eb7-ee96-<br>4562-8e5e-<br>f6b67ef63cdb |

### Product family datasheet

#### Download Data

#### File



User instruction NIGHT BREAKER LED START



User instruction
GPRS Safety symbols instructions

#### Legal advice

1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 60%3) In comparison to traditional Halogen lamps4) For precise conditions please refer to: www.osram.com/am-guaranteeApplication advice:

For more detailed application information and graphics please see product datasheet and user manual.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.