Product family datasheet

OSRAM

LEDriving SL W21W/5W YELLOW

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Amber



Replaces conventional W21W5W lamps Easy upgrade to LED technology with

plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W21/5W

LEDriving SL W21W/5W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional W21W/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Product in | Product information | | General Product Information | Electrical D | Electrical Data | |
|----------------------------------|---------------------------------------|-------------------------------|---|--|-------------------------------|-------------------------------------|--|
| Product description | | on (Category uct specific) | Product type (off- road vs. on-road) | Global order reference | Power input | Nominal voltage | |
| LEDriving SL ≜ W21/5W | Mainly us signal/ in applicatic | dicator | Off-road ≙ W21/5W | 7515DYP | 1.8 W | 12.0 V | |
| | | | | Photometric Data | | Physical Attributes & Dimensions | |
| Product description | Nominal | wattage | Test voltage | Nominal luminous flux | Luminous flux tolerance | Diameter | |
| LEDriving SL \triangleq W21/5W | 1 W | | 13.5 V | 55/10 lm | ±25 % | 20.0 mm | |
| | Lifetime [| Lifetime Data | | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | |
| Product description | Lifespan B3 | Lifespan Tc | Technology | Primary article identifier | Candidate | | |
| LEDriving SL ≙ W21/5W | 1500 hr | 4000 hr | LED ¹⁾ | 4052899520653 | Lead | | |

| Product description | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|-----------------------|---------------------------|---|---|
| LEDriving SL ≙ W21/5W | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 0224783a-4339- 4182-a700- 2fb236c75872 7fa03 599-7e48-4df0-ad7d- 163903f97f9f |

 $^{1)}$ Light-emitting diode lamp

Product family datasheet

Download Data

File

Image: Second s

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.