

BATTERYstart 400

Jump starters



Engine size compatibility

To jump start 12 V vehicles up to 8 L with petrol engines and 4 L with diesel



Battery Power

High Power 16,800 mAh Lithium Cobalt battery



Powerbank-Function

Charging electronic devices including smart phones and tablets



Compact and powerful lithium jump starter with power bank feature

The OSRAM BATTERYstart400 is a high power Lithium Cobalt LiCoO₂ jump starter for 12V vehicles up to 8L with petrol engines and 4L with diesel. Compact, without compromising on power, the BATTERYstart400 fits easily into the glovebox of your car – making it easier to use when in an emergency. The BATTERYstart400's intelligent clamps have anti-spike, reverse polarity and short circuit protection, keeping you, the car and the jump starter safe and in working condition. Also includes a power bank feature for charging electronic devices such as mobile phones and tablets and a bright LED working light. Ideal for all car sizes, SUVs, vans and motorcycles.

Product family datasheet

Technical data

| Product description | Product information | | | |
|---------------------|---------------------|--|--|------------------|
| | Efficiency | Recommended Petrol Engine size (up to) | Recommended Diesel Engine size (up to) | USB sockets 2.1A |
| BATTERY start 400 | Best | 8 l | 4 l | 2 |





| Product description | 12V Power socket connection | Application (Category and Product specific) | General Product Information | Physical Attributes & Dimensions |
|---------------------|-----------------------------|---|-----------------------------|----------------------------------|
| | | | Global order reference | Length |
| BATTERY start 400 | Yes | Lithium Starter | OBSL400 | 212.0 mm |

| Product description | Width | Height | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---------------------|---------|---------|--|------------------------|
| | | | Candidate list substance 1 | CAS No. of substance 1 |
| BATTERY start 400 | 88.0 mm | 30.0 mm | Lead | 7439-92-1 |

| Product description | Safe use instruction | Declaration no. in SCIP database |
|---------------------|--|--------------------------------------|
| BATTERY start 400 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 04bfb91c-9f38-4530-8bb1-23587637e9c4 |

Product family datasheet

Download Data

| File | |
|---|--|
|  | User instruction BATTERYstart |
|  | Movie application BatteryStart How to Video (ITA) |
|  | Movie application BatteryStart How to Video (EN) |
|  | Product movie OSRAM BATTERYstart 400 Product Video (EN) |

Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

— Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.