

Round VX80-WD



ECE certified - ECE R112

The necessary tests and approvals were carried out and an ECE type approval was granted. ECE reference number: 12.5



Wide Beam

Designed for a near field illumination. For large area illumination in the near field of the vehicle



Light beam up to 240 m length

See and be seen with OSRAM



On-road & Off-road

Versatile applicable and flexible in use. On-road & off-road, in terrain, at work and in the spare time.



Bringing light to life with OSRAM LEDriving driving and working lights

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Round VX80-WD. With its 4 powerful, high-performance long-life LEDs, the OSRAM LEDriving Round VX80-WD has a range of up to 240 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the OSRAM LEDriving Round VX80-WD with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 1150 lumens of luminosity scores with highest optical efficiency and homogeneous light distribution. This results in the possibility of an improved view for you and the improved visibility of your vehicle by other road users, and consequently also increased safety on-road and off-road. Whether on-road or off-road – The OSRAM LEDriving Round VX80-WD impresses with its powerful performance and a long service life with up to 5000 hours. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The OSRAM LEDriving Round VX80-WD has been tested and validated with the IP-Protection Class IP67 in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. The integrated driver and the thermal management system regulate the temperature of the OSRAM LEDriving Round VX80-WD and can thus prevent damage from overheating. The polarity protection inhibits the wrong polarity of the voltage supply and can thus prevent possible damage by automatically switching off the LEDs. On-road and off-road, the OSRAM LEDriving Round VX80-WD is an effective and efficient addition to your vehicle. No registration or entry in the vehicle documents is necessary for these ECE-certified LED driving lights²). ECE reference number: 12.5 The OSRAM LEDriving Round VX80-WD can be attached to cars, trucks, agricultural machinery, farm machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads²). The OSRAM LEDriving Round VX80-WD is versatile applicable and flexible in use.²) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

Product family datasheet

Technical data

Product description	Product information	General Product Information	Electrical Data	
	Application (Category and Product specific)	Global order reference	Nominal voltage	Nominal wattage
Round VX80-WD ¹⁾	Additional high beam application	LEDDL119-WD	12/24 V	24 W

Product description	Test voltage	Photometric Data	LED module information	Lifetime Data	Capabilities
		Nominal luminous flux	Number of LEDs per module	Lifespan Tc	Technology
Round VX80-WD ¹⁾	13.5 V	1150 lm	4	5000 hr	LED ²⁾

Product description	Certificates & standards			Logistical data
	Approval marks – approval	Type of protection	Standards	Commodity code
Round VX80-WD ¹⁾	E4 approval	IP67	ECE R10, R112	85122000900

Product description	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Date of declaration	Candidate list substance 1	CAS No. of substance 1	Safe use instruction
Round VX80-WD ¹⁾	19-08-2024	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.












Product description	Declaration no. in SCIP database
Round VX80-WD ¹⁾	d24869ff-3230-4b0b-9125-9296f06e8a68

¹⁾ Beam Pattern: Wide

²⁾ Light-emitting diode application

Product family datasheet

Download Data

File	
	User instruction LEDriving Round VX80-WD
	Movie application LEDriving D and W Image Video Bringing light to life (EN)
	Movie application Working and Driving Lights Amarok Winter
	Movie application LEDriving Driving and Working Lights Reference Video (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
	ref_pim_amsproduct360degreeimages Round VX80-WD LEDDL119-WD

Legal advice

Legal advice:

The installation of the OSRAM LEDriving Round VX80-WD is fully ECE compliant and therefore registration free. This does not include individual custom requirements of countries, in addition to the standardized ECE certification of the product.

1) Precise terms and conditions at: www.osram.com/am-guarantee

2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. Refer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.