## **OSRAM**

# LEDriving SL R5W

Ideal replacement for any vehicle



Suitable for various vehicle interior and exterior applications

Available in Cool White



Replaces conventional R5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for R5W

LEDriving SL R5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional R5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Product family datasheet

#### Technical data

|                                   | Product information                 |        |   | General Product<br>Information                             | Electrical Data  |                                  |
|-----------------------------------|-------------------------------------|--------|---|--|--|----------------------------------|
| Product description               | Application and Produc              |        | Product<br>type (off-<br>road vs.<br>on-road) | Global order<br>reference                                  | Power<br>input   | Nominal voltage                  |
| LEDriving SL ≙ R5W                | Mainly used signal/indi application | icator | Off-road ≙<br>R5W                             | 5007DWP  | 0.5 W  | 12.0 V                           |
|                                   |                                     |        |   | Photometric Data   |  | Physical Attributes & Dimensions |
|                                   |                                     |        |   |  |  |                                  |
| Product description               | Nominal wa                          | attage | Test<br>voltage                               | flux   | Luminous<br>flux<br>tolerance                                | Diameter                         |
| Product description  LEDriving SL | Nominal wa                          | attage |   | flux   | flux   | Diameter 19.0 mm                 |
|                                   |                                     |        | voltage                                       | flux   | flux<br>tolerance<br>±25 %<br>latory Inform<br>Art. 33 of EU | 19.0 mm                          |
|                                   | 0 W                                 |        | voltage                                       | flux  50 lm  Environmental & Regul Information according a | flux<br>tolerance<br>±25 %<br>latory Inform<br>Art. 33 of EU | 19.0 mm ation ) n no. in         |

4062172222808

<sup>1)</sup> Light-emitting diode lamp

#### Product family datasheet

#### Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

#### Safety advice

Canbus compatible

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.