

# XENARC NIGHT BREAKER LASER (NEXT GEN) D3S

Brightest OSRAM xenon light



**Up to 220% more brightness<sup>1), 2)</sup>**

More light allows to see farther and therefore react sooner compared to the minimum legal standard



**Up to 250 m long beam**

For better visibility



**Up to 20% whiter light<sup>1)</sup>**

More modern look compared to the minimum legal standard



**For more customer satisfaction**

3 year guarantee, refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions



## The most powerful xenon light from OSRAM

XENARC NIGHT BREAKER LASER is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER LASER - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.<sup>1)</sup> Compared to minimum ECE R98/R99 requirements<sup>2)</sup> D3S, D4S

# Product datasheet

## Technical data

### Product information

Product legal advice 1	1) Compared to minimum ECE R98/R99 requirements
Product legal advice 2	2) D3S, D4S

### Electrical data

Power input	35 W
Nominal voltage	42.0 V
Nominal wattage	35.00 W
Power input tolerance	±3 %
Test voltage	13.5 V

### Photometrical data

Luminous flux	3200 lm
Luminous flux tolerance	±15 %

### Dimensions & weight

Length	83.2 mm
Diameter	9 mm
Product weight	60.20 g

### Lifespan

Lifespan B3	2000 h
Lifespan Tc	3000 h

### Additional product data

Base (standard designation)	PK32d-5
-----------------------------	---------

### Capabilities

Technology	HID
------------	-----

### Certificates & standards

ECE category	D3S <sup>1)</sup>
Approval marks – approval	E1 approval

<sup>1)</sup> To be operated only with approved electronic control gear

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

## Product datasheet


Date of Declaration	08-03-2024
Primary Article Identifier	4052899631304   4052899631342
Declaration No. in SCIP database	In work

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899631304	XENARC NIGHT BREAKER LASER D3S	Hard Cover Box 2	114 mm x 49 mm x 106 mm	0.58 dm <sup>3</sup>	212.00 g
4062172313636	XENARC NIGHT BREAKER LASER D3S	Shipping carton box 4	122 mm x 106 mm x 121 mm	1.56 dm <sup>3</sup>	505.00 g
4062172313643	XENARC NIGHT BREAKER LASER D3S	Shipping carton box 48	371 mm x 256 mm x 232 mm	22.03 dm <sup>3</sup>	6308.00 g
4052899631342	XENARC NIGHT BREAKER LASER D3S	Folding carton box 1	53 mm x 46 mm x 93 mm	0.23 dm <sup>3</sup>	80.00 g
4062172313728	XENARC NIGHT BREAKER LASER D3S	Shipping carton box 4	115 mm x 101 mm x 103 mm	1.20 dm <sup>3</sup>	346.00 g
4062172313735	XENARC NIGHT BREAKER LASER D3S	Shipping carton box 48	371 mm x 256 mm x 232 mm	22.03 dm <sup>3</sup>	4401.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 Movie application Installation Video Xenarc Night Breaker Laser Opel Zafira (EN)

#### Safety advice

XENARC lamps should be replaced by a qualified mechanic.

This product must only be operated with approved electronic control gear.

#### Legal advice

Light output compared to the minimum ECE R98/99 requirements

This product must only be operated with approved electronic control gear

XENARC lamps should be replaced by a qualified mechanic

Reduced UV emission | For projection headlights | ECE approval and DOT label

± 450 lm

## Product datasheet

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# OSRAM