Product family datasheet

OSRAM

LEDriving HL BRIGHT HB4/HIR2



Up to +300% more brightness

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner. Compared to minimum ECE R112, for H7/H18 & H4/H19



Very compact LED replacement for conventional HB4HIR2 high and low beam lamps Reduced glaring thanks to an

optimized light distribution



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



4 year OSRAM guarantee

For precise conditions, please refer to www.osram.com/amguarantee





High-performing LED retrofit lamp providing improved visibility and a stylish look

With up to +300% more brightness (compared to ECE R112, for H7/H18 & H4/H19), the OSRAM LEDriving HL BRIGHT retrofit lamp ensures optimum visibility and thus allowing drivers to recognize signs, obstacles and hazards sooner than conventional lamps. This LED retrofit lamp not only creates a stylish modern look with a cool white color temperature of 6,000K but also offers reduced glaring thanks to an optimized light distribution. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to ECE R112) and better visibility thanks to daylight effect. The pair of lamps comes with a 4-year OSRAM guarantee. For precise guarantee conditions please refer to www.osram.com/am-guarantee.The LEDriving HL BRIGHT high and low beam lamps by OSRAM replace conventional halogen lamps and are 12V compatible. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product information		General Product Information		Electrical Data			
Product description	Product type (off- road vs. on-road)	Application (Category and Product specific)		Global order reference		Power input	Nominal voltage	
LEDriving HL BRIGHT ≜ HB4/HIR2	Off-road △Mainly used for Low9006DWBRT19 VHB4/HIR2Beam, High Beam and Fog light applicationsand Fog light				19 W	12.0 V		
	Photometric		Data		Physical Attributes & Dimensions		Lifetime	
						Dimens	ions	Data
Product description	Nominal watt	age	Nominal lum flux	inous	Luminous flux tolerance	Dimens		Data Lifespan Tc
Product description LEDriving HL BRIGHT ≜ HB4/HIR2	Nominal watt	age		inous	flux		er	Lifespan

Product description

LEDriving HL BRIGHT \doteq HB4/HIR2

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving HL BRIGHT ≙ HB4/HIR2	The identification of the Candidate List substance is sufficient to allow safe use of the article.	5f468c80-b523- 4b12-8251- 98417f190574

Candidate list

substance 1

Lead

CAS No. of substance

1

7439-92-1

Primary article

4062172315999

identifier

Technology

LED

Product family datasheet

Download Data

	File
*	User instruction LEDriving HL BRIGHT
Z	User instruction GPRS_Safety symbols instructions
7	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











