OSRAM

NIGHT BREAKER H1-LED

OSRAM's first NIGHT BREAKER H1 LED



Street-Legal1)

The NIGHT BREAKER LED family - OSRAM's first street-legal1) LED retrofit lamps.



6000K & Cool White

See and be seen with OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night



Up to 5 times longer lifetime 3)

Vibration resistant, environmentally friendly, and cost-efficient



4 year OSRAM guarantee

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



With the NIGHT BREAKER H1 LED OSRAM's first street legal1) H1-LED replacement lamp is now on the market

With the street-legal1) NIGHT BREAKER H1-LED you can now upgrade the function of your high- and low beam lights of your vehicle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional H1 lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with reduced glare for other road users that is up to 40% lower as the permissible maximum values2). In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 55% less energy and convince thanks to the LED technology and the specially developed vibration-resistant design, with up to 5 times longer life time3). You can now replace your vehicle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval1) Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps2)

Product family datasheet

Technical data

	Product in	formation							
Product description	Product legal advice		Product legal advice 2		Product legal advice 3		Application (Category and Product specific)		
NIGHT BREAKER H1 LED	light source applies to respective in which the approval of approval approval at the vehicle and light for currently leading to the compatibition more deta	1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-		2) In comparison to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 40%		3) Compared to halogen lamps		High and low beam	
	General Product Information		Electrical Data						
Product description	Global order reference		Power input	Power input toleranc e	Nominal wattage		Nominal voltage		
NIGHT BREAKER H1 LED	64150DW	64150DWNB		±15 %	16 W 1		12.0 V		
	Photomet	ric Data						Physical Attribut es & Dimensi ons	
Product description	Color tem	Color temperature		Nominal luminous flux		r Lumin flux tolera		Product weight	
NIGHT BREAKER H1 LED	6000 K		1550 lm		Cool white	±15 %		50.00 g	
							Lifeti	me Data	
Product description	Length	Length		Lamp base		Diameter		Lifespan Tc	
NIGHT BREAKER H1 LED	76.2 mm	76.2 mm		P14.5s		11.8 mm		2500 hr	
		Capabilities	Certificates & standards		Environmental & Reg Information according Regulation (EC) 1907		ng Art.	g Art. 33 of EU	
Product description	Lifespan B3	Technology	Standards		Primary article identifier			Candidate list substance 1	
NIGHT BREAKER H1 LED	1500 hr	LED	ABG		4062172373791		Le	ad	

Product family datasheet

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
NIGHT BREAKER H1 LED	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	903e3f51-c32d-4f87- bae4-4b7e9340d530

Product family datasheet

Download Data

	File
	User instruction NIGHT BREAKER LED H1 64150DWNB
*	User instruction GPRS_Safety symbols instructions
Z	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Legal advice

- 1) Approved LED light source only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led
- 2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 40%
- 3) In comparison to traditional Halogen lamps
- 4) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

