

LEDinspect DUAL CHARGE PAD



Wire-Free Technology

Simply place a compatible worklight on the charging pad to easily hold and recharge



Flexible mounting options

With strong magnets and screw holes built-in, you can easily attach the charging pad to toolboxes, workbenches and more



Built to last

IK08 and IP20 rated to survive the rigors of the professional workshop



The easiest way to recharge two inspection lamps

Removing the need to find and connect the correct charging cable, OSRAM's Wire-Free charging pad securely stores and recharges a pair of suitable inspection lamps, so they are ready when you are. This innovative design not only enhances convenience but also supports an uninterrupted workflow.

Product family datasheet

Technical data

	Product information	General Product Information	Physical Attributes & Dimensions		
Product description	Application (Category and Product specific)	Global order reference	Product weight		Length
CHARGING PAD	LED inspection lights	LEDIL424	220.00 g		202.2 mm
			Lifetime Data	Capabili	ities
Product description	Width	Height	Guarantee	Technol	logy
CHARGING PAD	106.0 mm	105 mm	2 years	LED	
	Environmental & Reg Information according	ulatory Information 3 Art. 33 of EU Regulation	(EC) 1907/200	6 (REACh))
Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction		Declaration no. in SCIP database
CHARGING PAD	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the		298f9330-2cce-45e2- 84a3-cadbe07428a5

article.

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



User instruction

LEDinspect SINGLE CHARGE PAD DUAL CHARGE PAD

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.