

Wire Harness AX 2LS



Connection of two light sources

Wire harness suitable for the installation of two light sources with one lighting function of the OSRAM LEDriving driving and working lights for 12 V vehicles



OnOff switch integrated

For installation in the vehicles cabin to switch the OSRAM LEDriving working lights on or off as required



Easy Installation

For easy installation of OSRAM LEDriving driving and working lights



Bringing light to life with OSRAM LEDriving driving and working lights

To support the installation of the OSRAM LEDriving driving and working lights, OSRAM has developed a special series with suitable accessories for them. With the OSRAM Wire Harness AX 2LS, the OSRAM LEDriving driving and working lights, can now be installed quickly and easily on the appropriate vehicle. The OSRAM Wire Harness AX 2LS is a wire harness that is suitable for the installation of two light sources with one lighting function. It also has an integrated on/off switch that can be installed in the vehicles cabin to switch the OSRAM LEDriving working lights on or off as required. The switch is only to be used for the OSRAM LEDriving working lights. The OSRAM Wire Harness AX 2LS is suitable for 12V vehicles. OSRAM also offers a 2-year guarantee¹⁾.

Product datasheet

Technical data


Product information

Order reference	LEDDL ACC 102
-----------------	---------------

Electrical data

Nominal voltage	12.0 V
-----------------	--------

Dimensions & weight



Product weight	348.00 g
Length	0.0 mm

Lifespan

Guarantee	2 years
-----------	---------

Country specific categorizations

Order reference	LEDDL ACC 102
-----------------	---------------

Logistical data

Commodity code	85444290900
----------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	16-05-2024
Primary Article Identifier	4062172147729
Declaration No. in SCIP database	In work

Logistical Data

Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172147729	Wire Harness AX 2LS	Folding carton box 1	175 mm x 82 mm x 177 mm	2.52 dm ³	398.00 g
4062172147736	Wire Harness AX 2LS	Shipping carton box 8	362 mm x 335 mm x 190 mm	23.04 dm ³	3629.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction LEDriving, Wire Harness AX 2LS
	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
	Movie application LEDriving Driving and Working Lights Reference Video (EN)

Legal advice:

1) Precise terms and conditions at: www.osram.com/am-guarantee

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

